

**VILNIUS
ILS Z RWY 19
(CAT A/B/C/D)**

54°30'N —
BELARUS

AIRAC AMDT 001/2023

INSTRUMENT
APPROACH
CHART - ICAO

AERODROME ELEV 649
HEIGHTS RELATED TO
THR RWY 19 - ELEV 649

APP 120.705
TWR 118.205
ATIS 125.805

VILNIUS
ILS Z RWY 19
(CAT A/B/C/D)

TABULAR DESCRIPTION

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)/ Time	Turn Direction	Altitude (FT)/ Flight level	Speed (KT)	VPA/TCH	Navigation Specification
IAF EKSAM, INITIAL APPROACH											
001	IF	EKSAM	—	—	8.3	—	—	+5000	-230	—	RNAV 1
002	TF	VI412	—	244(252.0)	8.3	6.0	—	+3000	-210	—	RNAV 1
IAF GEKBI, INITIAL APPROACH											
001	IF	GEKBI	—	—	8.3	—	—	+4000	-230	—	RNAV 1
002	TF	VI412	—	171(179.3)	8.3	4.4	—	+3000	-210	—	RNAV 1
IAF KOTOV, INITIAL APPROACH											
001	IF	KOTOV	—	—	8.3	—	—	+5000	-230	—	RNAV 1
002	TF	ETIKU	—	069(077.6)	8.3	7.7	—	+4000	—	—	RNAV 1
003	TF	VI412	—	104(111.9)	8.3	5.0	—	+3000	210	—	RNAV 1
MISSED APPROACH											
001	—	RW19	—	—	8.3	—	—	—	—	—	RNAV 1
002	CF	VI415	Y	194(201.8)	8.3	—	—	+2700	—	—	RNAV 1
003	DF	VI413	—	—	8.3	—	L	@5000	-210	—	RNAV 1
004	TF	VI407	—	011(019.5)	8.3	18.6	—	—	—	—	RNAV 1
005	TF	EKSAM	—	312(320.0)	8.3	5.1	—	+5000	-230	—	RNAV 1
006	HM	EKSAM	—	244(252.0)	8.3	1 min	R	+5000	-230	—	RNAV 1

FIX/POINTS	COORDINATES	FIX FORMATION
VNO	54 38 09.8N 025 17 37.1E	
GEKBI (IAF)	54 53 01.4N 025 24 24.6E	
EKSAM (IAF/MAHF)	54 50 28.1N 025 34 22.5E	
KOTOV (IAF)	54 48 48.5N 025 03 25.3E	
ETIKU	54 50 28.9N 025 16 28.8E	
VI412 (IF)	54 48 37.4N 025 24 30.6E	11.22 NM VNO ; BRG 193.64° / 10.74 NM IBK
FAP	54 44 24.0N 025 21 33.6E	6.65 NM VNO ; BRG 193.64° / 6.18 NM IBK
RW19	54 38 40.73N 025 17 34.99E	
VI415 (MATF)	54 29 35.8N 025 11 18.7E	
VI413	54 29 00.7N 025 29 23.8E	
VI407	54 46 34.0N 025 40 02.2E	
LOC IBK	54 36 59.4N 025 16 24.8E	
DME IBK	54 38 29.0N 025 17 34.2E	

Changes: chart name; coordinates of VI412, VI415 and FAP; procedures coding.